

- The energy-saving design minimizes running costs and eliminates consumables.
- Achieves high reliability and stable low humidity maintenance for a long period of time by using one or more advanced high-performance compact dry units.
- Long-term continuous operation is possible at room temperature, silence, and vibration.
- The special desiccant in the dry unit is semi-permanent and usually does not need to be replaced.
- By downsizing the unit, you can make full use of the inside of the refrigerator.
- Easy-to-use wide door (magnet packing type).
- AC200-240V is also easy (without transformer) available (option)

- The left and right two-door type has no central support, and it is easy to put in and take out horizontally long ones.
- Shelf board load capacity : 50kg/ 1 Shelf (160 ~ 510 型) 100kg/1 Shelf (930 ~ 1430 型)
- With urethane casters (930,1330,1430)、Adjuster (optional) can be installed.

The DD(PDX/HYP/DUS) type can now control the humidity simply by pressing the humidity setting button(external humidity controller).($\pm 6\%RH$)

There is no central support.
(All models with double doors)
Horizontal ones can be easily taken in and out.



photo is TDC-932-DD

TDC-932-DD (Outside depth 710mm)
TDC-932-AX (Outside depth 730mm)
(Inside depth 650mm)



photo is TDC-1332-DD

TDC-1332-DD (Outside depth 710mm)
TDC-1332-AX (Outside depth 730mm)
(Inside depth 650mm)



photo is TDC-1432-DD

TDC-1432-DD (Outside depth 710mm)
TDC-1432-AX (Outside depth 730mm)
(Inside depth 650mm)

Specifications

- In accordance with product improvement, the specifications may be altered without notice.
- Dimensions are indicated W(Width)×D(Depth)×H(Height) in mm respectively.

	TDC-932-DD / TDC-932-AX	TDC-1332-DD / TDC-1332-AX	TDC1432-DD / TDC-1432-AX
Dehumidification / humidity control	Dry-unit • DD: Digital controller / AX: Dial automatic adjustment type		
External dimensions (m / m)	DD: 1,200×710×1,305 / AX: 1,200×730×1,305 (Including casters)	TDC-1309-DD: 1,200×710×1,855 TDC-1309-AX: 1,200×730×1,855 (Including casters)	TDC-1409-DD: 1,200×710×1,845 TDC-1409-AX: 1,200×730×1,845 (Including casters)
Internal dimensions (m / m)	1,198(1,130)×650×1,075(480×2)	1,198(1,130)×650×1,620(480×3)	1,198(1,130)×650×1,620(755×2)
Internal capacity	837 ℓ		1,261 ℓ
Cabinet material	Steel, powder coating, silver metallic		
Door / Hygrometer	Steel, Glass, Magnet rubber(PCV), Analog dual hygrometer(AX), Digital dual hygrometer(DD), Lock, Handle		
Power supply (AC220V) power consumption	AC100V (50/60Hz)		
	0~14.4W (MAX480W)		0~18W (MAX600W)
Weight (Kg)	150		210
Accessories	3 shelves, 2 keys, 4 casters (with front wheel stopper) level		5 shelves, 2 keys, 4 casters (with front wheel stopper) level

※PVC : Polyvinyl chloride

(Note) The dry cabinet does not have functions such as humidification (increasing humidity) and cooling / heating (increasing or decreasing the temperature) inside.
● Analog hygrometer accuracy: 20~80% RH $\pm 5\sim 7\%$ RH ■ MAX ○○○ W display of power consumption is only at the moment of startup.