"DRY-CABI" with reel rack

We also manufacture dry cabinets "Reel Rack Storage" according to your desired size.







Production example

 ϕ 600 reel rack 25 (20 kg / piece) storage Capacity: about 700 l 600kg load capacity Humidity 5% RH or less Antistatic type




Feeder storage

DRY-CABI for feeders of each company It is also possible to manufacture a shelf board.





 ϕ 800 reel rack 28 (60 kg / piece) storage Capacity: about 2,000 l Load capacity 1,800 kg Humidity 5% RH or less Antistatic type



Beware of maintenance and storage methods for molds and metal products!

Occurrence of rust, mold clearance, product accuracy quality It has a big impact.

Rust gradually occurs from around 40% RH, and at 65% RH rapidly Increase So-called hot and humid weather conditions with a temperature of at least 20 ° C and a humidity of at least 65% RH In this case, corrosion (rust) is very likely to occur.

DRY-CABI can meet various requests.(OPTIONS)

- 1 It can be manufactured in the desired special size.
- 2 The humidity setting conditions can be changed by making the upper and lower stages separate (separate room) type.
- With a load bearing type, 100 to 200 kg per shelf board, a total load of 1000 kg is also possible. (For storage of molds and special raw materials)
- 4 It is also possible to apply conductive paint and electromagnetic shielding paint. 8 It is also possible to manufacture stainless steel shelf boards and stainless steel bodies
- N2Gasket N Flow meter, alarm function etc. can also be mounted.
- 6 Reel rack, slide type shelf board, installation of wrist strap
- **7** Earthquake-resistant specification, with adjuster bolt, adjuster foot It is also possible to attach a caster, a connection bracket, and a fall prevention bracket.