

**World first**

Water supply unnecessary  
New humidification system  
**WET-CABE**  
Desiccant humidity absorption  
Humidification system

**ウェットキャベ**  
**WET-CABE**

**Humidification by humidity in the air is achieved.**  
Adjust the high performance dehumidifier by its own humidity control equipment,  
We realized new humidification system.

- The energy-saving design has the lowest running cost and no consumables.
- Achieves high reliability and stable low humidity maintenance for a long period of time by using one or more advanced high-performance compact dry units.
- Long-term continuous operation is possible at room temperature, silence, and vibration.
- The special desiccant in the dry unit is semi-permanent and usually does not require replacement.

- Easy-to-use wide door (Magnet packing type)
- The left and right two-door type has no central support, and it is easy to put in and take out horizontally long ones.
- Shelf load capacity 50kg/shelf (162~512), 100kg/shelf (932~1432).
- Available with urethane casters and adjusters.
- **AC200-240V is also easy (without transformer) available (option)**

※Seismic measures: Fall prevention bracket mounting bolts

**★Various uses★**  
Warpage prevention (Film, Paper, Wood)  
Prevention of dry destruction  
(Cultural, Old books, Wooden instruments)  
Antistatic  
(Electronic components, Precision equipment)  
High humidity storage (Cigar)  
For constant humidity experiment

**NEW With digital control!** It is easy to use with high precision.



**WET-1332-AHU**  
(Inside depth 650mm)



**WET-1432-AHU**  
(Inside depth 650mm)

**Specification**

● In accordance with product improvement, the specifications may be altered without notice.  
● Dimensions are indicated W(Width)×D(Depth)×H(Height) in mm respectively.

	<b>WET-1332-AHU</b>	<b>WET-1432-AHU</b>
Dehumidification / humidity control	Dry-unit/ digital controller desiccant humidity absorption system	
External dimensions (m / m)	1,200×748×1,855 (Includes caster)	1,200×748×1,845 (Includes caster)
Internal dimensions (m / m)	1,198(1,130)×650×1,620(480×3)	1,198(1,130)×650×1,620(755×2)
Internal capacity	1,261 ℓ	1,261 ℓ
Cabinet material	Steel, powder coating, silver metallic	
Door / Hygrometer	Steel, Glass, Magnet rubber(PCV), Digital dual hygrometer, Lock, Handle	
Power supply (AC220V) power consumption	AC100V (50/60Hz)	
Weight (Kg)	0~28.8W (MAX720W)	0~28.8W (MAX720W)
Accessories	5 shelves, 2 keys, 4 casters (with front wheel stopper) level	

※There is no heating function and cooling function

※Please consult us when using it under 30% RH environment humidity.

■ Hygrometer monitoring range and Accuracy: At 1~99%RH(±3~4.5%)  
■ Power consumption max shown is only at start up. \*AC200~240V is also available.

■ Separate type is possible for each of the upper and lower doors. (Humidity 20-30% RH on the top, humidity 50-60% RH on the bottom, etc.)