

- It is a simple, constant humidity tank that is humidified with only the moisture in the air. I do not need water supply.
- It holds 50 to 75% RH in the storage space all year round.
Humidity setting range: 50 to 75% RH Accuracy: ± 3 to 5% RH
- It is an energy saving type. Electricity only 30 yen ~ / month.
- With LED lamp lighting to light up the interior brightly and softly.
Angle-friendly to eyes, with external switch, length 600 to 1000 mm
- With power outlet inside and outside the cabinet. (Up to a total of 800W. AC100V)
- Silence, no vibration ■ Long-lasting High reliability Safe with 35 years of experience and results.

Even when high humidity
Even when dry

Spring Summer Autumn Winter

All year round
Comfortable humidity
(50~75% RH)
Safe storage

USE	50~60%RH	Storage	Art, Ancient Documents, Prints, Crafts, Scripture, Buried Cultural Properties, Excavated Goods, Lacquerware, Paper Products
	50~60%RH	Storage	Stringed instruments, guitars, violins, ukulele, shamisen, wood and wind instruments
	50%RH	Storage	Anti-static measures, electronic parts, precision parts, various products, parts
	50~75%RH	Storage	For various experiments
	70%RH	Storage	Cigar humidior

With digital control
High precision

Uses new digital controller and high-precision humidity sensor
(manufactured by Sensirion)



Humidity setting range : 50~75%RH Humidity display range : 0.0~99.9%RH(±3~4.5%RH)



WET-112



WET-202



WET-182



WET-322

Specification

- In accordance with product improvement, the specifications may be altered without notice.
- Dimensions are indicated W(Width)×D(Depth)×H(Height) in mm respectively.

TYPE	WET-112	WET-202	WET-182	WET-322
External dimensions	W400×D391×H933	W805×D428×H990	W400×D428×H1330	W805×D428×H1390
Effective dimension	W398×D320×H838	W803×D320×H790	W398×D320×H1235	W803×D320×H1234
Capacity	107 ℓ	203 ℓ	157 ℓ	317 ℓ
Humidity control	Dry unit Desiccant moisture absorption / dehumidification system Digital controller Digital display			
Body material	Steel Color : black			
Door	PVC frame, Glass, Magnet packing (PVC), Lock handle			
Power consumption	AC100V 0~11.2W MAX 120W	AC100V 0~18.8W MAX 240W	AC100V 0~13.2W MAX 120W	AC100V 0~22.8W MAX 240W
	Changeable to 200v~240V specifications, please consult.			
Product weight	17kg	37kg	26kg	55kg
Accessories	4 shelf boards LED 600mm 1	3 shelf boards LED 600mm 2	5 shelf boards LED 1000mm 1	5 shelf boards LED 1000mm 2
	100V outlet (inside 1 outside 1), key 2			

- If the internal humidity does not rise to the set humidity due to the season or environment, use the optional "humidifying liquid".

※Please consult us when using it under 30% RH environment humidity.