

Convenient option

Mounting frame (SUS430) (Easy assembly type)

■ Load capacity (Top plate 200Kg Shelf 200Kg Total load 350Kg)

TDC-162	AB6045	W600×D450×H500~800
TDC-302	AB9045	W900×D450×H500~800
TDC-512	AB9075	W900×D750×H500~800
TDC-932	AB12075	W1,200×D750×H500~800



Options

- Shelf board can be added
- Available on castors
- SUS-304 available

■ Alarm buzzer & lamp


- Door open / close alarm device
Prevents humidity changes in the cabinet by forgetting to close the door and preventing the door from opening for a long time.



※ There is also a method of detecting humidity changes and notifying with an alarm.

■ Analog hygrometer

- M II / NT hygrometer (With thermometer)
- Dual hygrometer (With thermometer)
Inside and outside humidity I also understand.



■ Lens mat

(Rolling prevention, fall prevention)
(Material: Polyethylene foam)

Big (4 groove)

Usable for PH series



Small (3 groove)

Available for all models



■ LED light with human sensor DC-4LED-IR

(Interior lighting)



■ Digital hygrometer

TYPE : H-5075-SD

2 months data display in the app. With a Bluetooth connection, you can check the temperature and humidity status and modify the settings from a remote location (within 50m).

You can also send data in CSV file format to an email with Data Export.



Humidity display range: 5% - 99% Humidity accuracy: ± 3% RH
Temperature accuracy: Temperature ± 0.3 °C / ± 0.54 °F
Temperature display range: 0 °C ~ 50 °C / 32 °F ~ 122 °F
Bluetooth distance: 50 meters
Battery: AAA batteries x 2
Dimensions (W x D x H): 65 x 22 x 80 mm
Sensirion SHT30 sensor

■ High performance digital Humidity meter

MD8102-DC (Transmitter)

Built-in logging function
High-performance hygrometer



Receiving machine MD-8000R-DC

Data recorded by the reception logging function Graph display on PC, data Display a list.

Measurement data Wireless transmission

